

Model A550

Weighing Indicator



FEATURES

- 200,000 Display Division
- Support up to 350 Ohms X 8 Load Cell
- Dual Weight Display and Increment
- RS232C Communication Port as Standard
- 49mm High Display, Green Or Red
- Basic Functionality: ZERO, TARE, CLEAR And PRINT
- ABS Plastic Housing With IP54 Protection
- Print And Totalization
- Auto Save Battery And Battery Indicating

OPTIONAL FEATURES

- 1 Input/3 Outputs (Relay)
- RTC (Real Time Clock)

APPLICATIONS

- Platform Scales
- Truck Weighbridge scales

SPECIFICATIONS	
Accuracy Class	III
EU Approval	200,000 Display Division
Display	6 bits 49mm high green display and 10 status lights
Update Speed	100ms
Status Display	Over/Under/OK, Count KG/LB, Center of Zero, Net/Gross, Motion, Battery
Key	5 function keys (TARE, CLEAR, ZERO, FUNCTION KEY, PRINT)
Power On/Off	Support
Type	24-bit
Speed	100 Hz
Resolution	0.05uV/d
Resolution Approved	1uV/e
Input	0.1mV to 19mV
Accuracy	200,000d
Load Cell Number	Max 8 x 350Ω
Exciting Voltage	5V DC
Connect Type	4- wired or 6-wired , Cable:274mR/m2
Basic Weighting	Tare ,Zero ,Print, Auto Tare, Auto Clear and Auto Print, Unit switch
Housing	IP54, Round housing bracket or Wall housing bracket
Temperature	-10 - 40°C , 95%RH
Power Supply	110VAC ~ 220VAC, 12W